



S007 FLEXIBLE WATERPOOF SLURRY

This product is a two-component acrylic polymer modified cement-based waterproof material, good adhesion to the substrate, excellent water resistance, mold resistance, wet operation, applicated for the ground waterproof.

TECHNICAL DATA

Product Name:	S007 FLEXIBLE WATER PROOF SLURRY
Product Code:	S007A
Type:	Water-based emulsion paint
Appreance:	Liquid material+Powder
Main Components:	Acrylic emulsion+Modified cement- based compound
Color:	Blue
Finish:	Mat
Volume:	20KG/bucket
Brushing Area:	1.3 kg/m ² (2 coats)
Malleability:	1 : 1.8
Pressure Resistance:	0.8MPa
Bonding Strength:	0.9MPa
Product Standard:	GBT23445-2009
Shelf Life:	24 months
Drying Time:	4 hours
Interval Time:	72 hours
(of tiling producre)	
Stability of Diluted Paint:	4-6 hours
Dilution:	Liquid: Powder=1:1.5

Application:

Wet or dry masonry, mortar, concrete, metal, wood, insulation layers, waterproofing layers (eg asphalt, rubber, SBS, APP, polyurethane, etc.)

Advantages:

- ◆ Anti-mildew
 - ◆ Anti-algae
 - ◆ Anti-cracking
 - ◆ Water and stain resistance
-

Application Conditions/ Limitations:

Surface preparation

- ◆ For repainting: Clean the surface till it is free from dust, grease and flaking paint from surface.Any unstable paint to be removed , using high pressure wash or scraper whichever is appropriate.
- ◆ New plaster: Ensure surface is completely cured and dry.Application of cement paint/lime as undercoat is not recommended.

Construcion Temperature: 10°C~ 45°C

GUANGDONG SHILIDE BUILDING MATERIAL CO. LTD.

#27-33, Floor 3rd , Block 6, Meiju Building Materials City, Lvjing West Road, Foshan, Guangdong, China
Ph: +86 0757 82726219 Email: exp@shilide.com.cn Website: www.shilide.com.cn

Dew Point:	◆ Beware of condensation! ◆ Substrate temperature during application must be at least 10°C above dew point.
Storage condition	24 months from date of production if stored properly in original unopened, sealed and undamaged packaging in cool and dry conditions at temperatures between +5°C and +25°C. Protect from direct sunlight.

Application Instructions:

1. Clean up the water and dust.
2. Open the bucket, stir the slurry and powder evenly.
3. First brushing horizontally by a brush or roller.
4. Second brushing vertically after drying.

Safety health & Environmental information

During painting	Always work in a well ventilated area. Wear appropriate attire, especially gloves and eye protection gear. Avoid contact with skin as it may cause irritation.
-----------------	--

Cleaning	Wash all the tools with water immediately after application
----------	---

Safety instructions	In case of eye contact, rinse immediately with water and seek immediate medical treatment. To remove paint for skin, use soap and water or appropriate cleanser. In the event of spillage, contain and collect spilt paint by using sand or earth.
---------------------	--

Environment:	Does not contain any added lead, mercury or chromium compounds.
--------------	---

GUANGDONG SHILIDE BUILDING MATERIAL CO. LTD.

#27-33, Floor 3rd , Block 6, Meiju Building Materials City, Lvjing West Road, Foshan, Guangdong, China
Ph: +86 0757 82726219 Email: exp@shilide.com.cn Website: www.shilide.com.cn