



S007 RIGID WATER PROOF SLURRY

This product is a two-component polymer modified cement-based waterproof material, good adhesion, excellent waterproof, penetration and compression performance. Applied for wall facade waterproofing.

TECHNICAL DATA

Product Name:	S007 RIGID WATER PROOF SLURRY
Product Code:	S007
Type:	Water-based emulsion paint
Appearance:	Liquid material+Powder
Main Components:	Butylbenzene emulsion+Modified cement- based compound
Color:	Green
Finish:	Mat
Volume:	20KG/bucket
Brushing Area	1.8 kg/m ² (2 coatings)
Shelf Life:	24 months
Drying Time:	4 hours
Interval Time (of tiling producre)	72 hours
Stability of Diluted Paint:	4-6 hours
Dilution:	Liquid: Powder=1:2.7

Application:

- ◆ Apply to the processing resistant to moisture and penetration
 - ◆ The interior and exterior cement concrete/cement brick wall/ light brick wall structure/ basement/ warehouse/ underground parking/ subway station/ tunnel/ civil air-defense shelters/ mine/ building foundation, flower groove, floor
 - ◆ Drinkable water pool/ swimming pool/pond/sewage treatment pool
-

Advantages:

- ◆ Strong adhesion
 - ◆ Excellent penetration and compression performance
 - ◆ Construction possible back or contacting with the water.
 - ◆ Tile pasting directly
-

Application Conditions/ Limitations:

Surface preparation

- ◆ For repainting: Clean the surface till it is free from dust, grease and flaking paint from surface. Any unstable paint to be removed, using high pressure wash or scraper whichever is appropriate.
- ◆ New plaster: Ensure surface is completely cured and dry. Application of cement paint/lime as undercoat is not recommended.

Construction Temperature: +10°C min. / +45°C max.

Dew Point:


- ◆ Beware of condensation!
- ◆ Substrate temperature during application must be at least 10°C above dew point.

GUANGDONG SHILIDE BUILDING MATERIAL CO. LTD.

#27-33, Floor 3rd, Block 6, Meiju Building Materials City, Lvjing West Road, Foshan, Guangdong, China
Ph: +86 0757 82726219 Email: exp@shilide.com.cn Website: www.shilide.com.cn

Storage condition 24 months from date of production if stored properly in original unopened, sealed and undamaged packaging in cool and dry conditions at temperatures between +5°C and +25°C. Protect from direct sunlight.

Application Instructions:



1. Base processing
 2. Do the protection of the construction contact surface
 3. Allocate the paint and stir evenly
 4. Two times is recommended (horizontally and vertically brushing per once).
 5. Tiling directly after 72 hours drying of this paint.
-

Safety health & Environmental information

During painting Always work in a well ventilated area. Wear appropriate attire, especially gloves and eye protection gear. Avoid contact with skin as it may cause irritation.

Cleaning Wash all the tools with water immediately after application

Safety instructions In case of eye contact, rinse immediately with water and seek immediate medical treatment. To remove paint for skin, use soap and water or appropriate cleanser. In the event of spillage, contain and collect spilt paint by using sand or earth.

Environment: Does not contain any added lead, mercury or chromium compounds.

GUANGDONG SHILIDE BUILDING MATERIAL CO. LTD.

#27-33, Floor 3rd , Block 6, Meiju Building Materials City, Lvjing West Road, Foshan, Guangdong, China
Ph: +86 0757 82726219 Email: exp@shilide.com.cn Website: www.shilide.com.cn