



HEALTHY WATER-BASED FLOOR PAINT

This product is a water-based and environmental friendly floor paint, used high molecular polymer, inorganic functional materials as the base material, water as the dispersion medium. Apply to the resistance to moisture of the wood floor basement.

TECHNICAL DATA

Product Name:	HEALTHY WATER-BASED FLOOR PAINT
Product Code:	S6150
Type:	Water-based emulsion paint
Appearance:	Green paste
Main Components:	Styrene-Acrylic Emulsion+ Calcium carbonate (CaCO ₃)
Color:	Green
Finish:	Matt
Volume:	8 KG/bucket
Brushing Area:	3.5 m ² /kg (2 coats)
Product Standard:	GB 18582-2008 ; GB/T 9756-2009
Shelf Life:	18 months
Surface Drying Time:	4 hours
Drying Time:	24 hours
Stability of Diluted Paint:	48 hours

Application:

Apply to the wall sealing, the moisture-proof, waterproof and mildew-proof processing before wallpaper (can also be used for wardrobe, decorative cabinet and board waterproofing moisture-proof treatment.).

Advantages:	<ul style="list-style-type: none">◆ Excellent performance of alkali resistance◆ Good adhesion◆ Abrasion resistance◆ Strong covering power◆ No odors◆ No heavy metals
--------------------	---

Application Conditions/ Limitations:

Surface preparation:	◆ For repainting: Clean the surface till it is free from dust, grease and flaking paint from surface. Any unstable paint to be removed, using high pressure wash or scraper whichever is appropriate. ◆ New plaster: Ensure surface is completely cured and dry. Application of cement paint/lime as undercoat is not recommended.
Dilution(kg):	Water diluted less than 20%
Construction Temperature:	5°C~45°C.
Construction Humidity:	≤85%
Dew Point:	◆ Beware of condensation! ◆ Substrate temperature during application must be at least 5°C above dew point.
Storage condition	18 months from date of production if stored properly in original unopened, sealed and undamaged packaging in cool and dry conditions at temperatures between +5°C and +25°C. Protect from direct sunlight.

Application Instructions:



1. Clean the substrate.
2. Brush the paint 1 time.
3. Brush the second time after drying (after 2 hours of the first coating).
4. Next construction process after 24 hours drying completely.

Safety health & Environmental information

During painting	Always work in a well ventilated area. Wear appropriate attire, especially gloves and eye protection gear. Avoid contact with skin as it may cause irritation.
Cleaning	Wash all the tools with water immediately after application
Safety instructions	In case of eye contact, rinse immediately with water and seek immediate medical treatment. To remove paint for skin, use soap and water or appropriate cleanser. In the event of spillage, contain and collect spilt paint by using sand or earth.
Environment:	Does not contain any added lead, mercury or chromium compounds.

GUANGDONG SHILIDE BUILDING MATERIAL CO. LTD.

#27-33, Floor 3rd, Block 6, Meiju Building Materials City, Lvjing West Road, Foshan, Guangdong, China
Ph: +86 0757 82726219 Email: exp@shilide.com.cn Website: www.shilide.com.cn