



SOLID WALL PAINT

This product is a new kind of water-soluble polymer, appearance milky white glue. This product has excellent permeability, can fully infiltrate the wall surface, make the basement density, improve the adhesion of smooth interface. Apply to the wall sealing of the wall base surface or old wall renovation .

TECHNICAL DATA

Product Name:	SOLID WALL PAINT
Product Code:	S6500
Type:	Water-based styrene-acrylic emulsion
Appearance:	Liquid
Main Components:	Styrene-Acrylic Emulsion
Color:	White
Finish:	Transparent
Volume:	8 KG/bucket
Brushing Area:	7m ² /kg (2 coats)
Hardness:	3H
Abrasion Resistance:	Resistant to scrubbing 600 times
Product Standard:	GB 18582-2008; GB/T 9756-2009
Shelf Life:	18 months
Interval Time:	6 hours
(for second coat)	
Stability of Diluted Paint:	48 hours

Application:

The construction of the walls like concrete, brick, gypsum board, composite board and old walls.
The interior decoration.

Advantages:

- ◆ Waterproof
 - ◆ Moisture resistance
 - ◆ Enhance the hardness of the concrete surface
 - ◆ High solid content
 - ◆ Big brushing area
-

Application Conditions/ Limitations:

Surface preparation:	<ul style="list-style-type: none">◆ For repainting: Clean the surface till it is free from dust, grease and flaking paint from surface. Any unstable paint to be removed, using high pressure wash or scraper whichever is appropriate.◆ New plaster: Ensure surface is completely cured and dry. Application of cement paint/lime as undercoat is not recommended.
Dilution(kg):	Water diluted less than 20%
Construction Temperature:	5°C~45°C.
Construction Humidity:	≤85%
Dew Point:	<ul style="list-style-type: none">◆ Beware of condensation!◆ Substrate temperature during application must be at least 5°C above dew point.
Storage condition	18 months from date of production if stored properly in original unopened, sealed and undamaged packaging in cool and dry conditions at temperatures between +5°C and +25°C. Protect from direct sunlight.

Application Instructions:



1. Brush directly on the original cement base, no leaking area. 1 coating is enough.
2. Application by brush, roll and spray. Stir evenly before construction if diluting water.
3. Multiple coating available.
4. The construction interval should be more than 6 hours.

Safety health & Environmental information

During painting	Always work in a well ventilated area. Wear appropriate attire, especially gloves and eye protection gear. Avoid contact with skin as it may cause irritation.
Cleaning	Wash all the tools with water immediately after application
Safety instructions	In case of eye contact, rinse immediately with water and seek immediate medical treatment. To remove paint for skin, use soap and water or appropriate cleanser. In the event of spillage, contain and collect spilt paint by using sand or earth.
Environment:	Does not contain any added lead, mercury or chromium compounds.

GUANGDONG SHILIDE BUILDING MATERIAL CO. LTD.

#27-33, Floor 3rd, Block 6, Meiju Building Materials City, Lvjing West Road, Foshan, Guangdong, China
Ph: +86 0757 82726219 Email: exp@shilide.com.cn Website: www.shilide.com.cn