



FULL-EFFECT MOISTUREPROOF PAINT

This product has two kinds of yellow and transparent liquid. Good hardness, high gloss, anti-ultraviolet, aging resistance, high permeability, anti-cracking, waterproof, moisture-proof, anti-mildew. Its moisture and flame resistance function is permanent. Apply to the moisture-proof processing of wallpaper, board, gypsum board, stone, furniture, door cover, interior and exterior wall, etc..

TECHNICAL DATA

Product Name:	FULL-EFFECT MOISTUREPROOF PAINT
Product Code:	S6600
Type:	Water-based styrene-acrylic emulsion
Appearance:	Liquid
Main Components:	Styrene-acrylic emulsion
Color:	Yellow
Finish:	Yellow & Transparent
Volume:	8 KG/bucket
Brushing Area:	12m ² /kg (2 coats)
Solid Content:	0.354
Product Standard:	GB 18582-2008; GB/T 9756-2009
Shelf Life:	18 months
Surface Drying Time:	0.5 hours
Interval Time:	12 hours
(for second coat)	
Drying Time:	24 hours
Stability of Diluted Paint:	48 hours

Application:

Apply to the waterproof, moisture-proof, anti-mildew processing before the wallpaper pasting. Also applicable to the moisture-proof processing between the wardrobe, cabinets, decorative board, door cover and the wall.

Advantages:

- ◆ High transparency
 - ◆ Good preservation
 - ◆ Abrasion resistance
 - ◆ Speedy filming
 - ◆ Environmental friendly anti-mildew agent
 - ◆ Ultra anti-moisture
-

Application Conditions/ Limitations:

Surface preparation:	<ul style="list-style-type: none">◆ For repainting: Clean the surface till it is free from dust, grease and flaking paint from surface. Any unstable paint to be removed, using high pressure wash or scraper whichever is appropriate.◆ New plaster: Ensure surface is completely cured and dry. Application of cement paint/lime as undercoat is not recommended.
Dilution(kg):	1 : 1
Construction Temperature:	5°C~45°C.
Construction Humidity:	≤85%
Dew Point:	<ul style="list-style-type: none">◆ Beware of condensation!◆ Substrate temperature during application must be at least 5°C above dew point.
Storage condition	18 months from date of production if stored properly in original unopened, sealed and undamaged packaging in cool and dry conditions at temperatures between +5°C and +25°C. Protect from direct sunlight.

Application Instructions:



1. Clean the dust on the surface before brushing
2. Brush after drying.
3. Normally brushing once can achieve the desired effect, 2 times better.
4. No soaking within brushing 24 hours.

Safety health & Environmental information

During painting	Always work in a well ventilated area. Wear appropriate attire, especially gloves and eye protection gear. Avoid contact with skin as it may cause irritation.
Cleaning	Wash all the tools with water immediately after application
Safety instructions	In case of eye contact, rinse immediately with water and seek immediate medical treatment. To remove paint for skin, use soap and water or appropriate cleanser. In the event of spillage, contain and collect spilt paint by using sand or earth.
Environment:	Does not contain any added lead, mercury or chromium compounds.

GUANGDONG SHILIDE BUILDING MATERIAL CO. LTD.

#27-33, Floor 3rd, Block 6, Meiju Building Materials City, Lvjing West Road, Foshan, Guangdong, China
Ph: +86 0757 82726219 Email: exp@shilide.com.cn Website: www.shilide.com.cn