



ANION FULL-EFFECT INTERIOR WALL PAINT

This product is used high-quality imported raw material, special additives and adsorption functional materials, advanced production technology. Apply to interior decoration of house, villas, luxury hotels,

TECHNICAL DATA

Product Name:	ANION FULL-EFFECT INTERIOR WALL PAINT
Product Code:	S8800
Type:	Water-based emulsion paint
Appearance:	White paste
Main Components:	Styrene-acrylic emulsion+CaCO ₃ +TiO ₂
Color:	White
Finish:	Sheen
Volume:	6 KG/bucket
Brushing Area:	6m ² /kg (2 coats, film thickness of single coating-30μm)
Abrasion Resistance:	>300 times
Product Standard:	GB 18582-2008; GB/T9756-2009
Shelf Life:	18 months
Surface Drying Time:	0.5 hours
Interval Time:	2 hours (Film thickness 30μm, 25-30°C)
(for second coat)	
Drying Time:	1 hours
Curing Time:	7 days
Stability of Diluted Paint:	48 hours
Dilution:	S8800: Water=1:0.2

Application:

Apply to interior decoration and protection of the villas, hotels, office buildings and houses.


Advantages:

- ◆ No odors
 - ◆ Anti-mildew and anti-bacterial
 - ◆ Excellent alkali resistance
 - ◆ Abrasion resistance
 - ◆ Negative ions release
 - ◆ Formaldehyde decomposition and absorption
-

Application Conditions/ Limitations:

Surface preparation:	<ul style="list-style-type: none">◆ For repainting: Clean the surface till it is free from dust, grease and flaking paint from surface. Any unstable paint to be removed, using high pressure wash or scraper whichever is appropriate.◆ New plaster: Ensure surface is completely cured and dry. Application of cement paint/lime as undercoat is not recommended.
Construction Temperature:	5°C~45°C.
Construction Humidity:	≤85%
Dew Point:	<ul style="list-style-type: none">◆ Beware of condensation!◆ Substrate temperature during application must be at least 5°C above dew point.
Storage condition	18 months from date of production if stored properly in original unopened, sealed and undamaged packaging in cool and dry conditions at temperatures between +5°C and +25°C. Protect from direct sunlight.

Application Instructions:



1. Apply the putty (3 coats is appropriate).
2. Polish the surface.
3. Clean the dust.
4. Take out the appropriate product, dilute 20% water and stir evenly.
5. Brush the second time after 2 hours drying of the first time brushing.

Safety health & Environmental information

During painting	Always work in a well ventilated area. Wear appropriate attire, especially gloves and eye protection gear. Avoid contact with skin as it may cause irritation.
Cleaning	Wash all the tools with water immediately after application
Safety instructions	In case of eye contact, rinse immediately with water and seek immediate medical treatment. To remove paint for skin, use soap and water or appropriate cleanser. In the event of spillage, contain and collect spilt paint by using sand or earth.
Environment:	Does not contain any added lead, mercury or chromium compounds.

GUANGDONG SHILIDE BUILDING MATERIAL CO. LTD.

#27-33, Floor 3rd, Block 6, Meiju Building Materials City, Lvjing West Road, Foshan, Guangdong, China
Ph: +86 0757 82726219 Email: exp@shilide.com.cn Website: www.shilide.com.cn