



## 5.0mm Round Type LED Lamps

Model No.: **5R94EYC-8BA**

ECN: \_\_\_\_\_

Page: 1/5

### Features :

- Two chips are matched for uniform light output, wide viewing angle
- Long life-solid state reliability
- I.C. compatible/Low power consumption

### Descriptions :


- The series is specially designed for applications requiring higher brightness.

- The led lamps are available with different colors, intensities epoxy colors,etc.

### Applications :

- TV set
- Monitor
- Telephone
- Computer

### Package Dimensions:



**Notes:** 1. All dimensions are in millimetres

2. An epoxy meniscus may extend about 1.5mm(0.059") down to the lead.

3. Tolerances unless Dimension  $\pm 0.25$ mm.

PART NO.	Chip		Lens Color
	Material	Emitted Color	
5R94EYC-8BA	GaAsP/GaP	Orange	Water Clear
	AlGaInP	Super Yellow	

Address: Building 2, The First Business Estate, 1th Mingying Rd, shiqidistrict, Zhongshan, Guangdong, China.

TEL : (+86 760) 88323449 88324139

FAX : (+86 760) 88321064 88235016

E-mail: sales @ silsmart.com

Prepared by: David

Prepared date: 14/12/16

M01M01

BZ121010



# 中山市晶明光电科技有限公司

## ZHONSHAN SILSMART OPTOELECTRONICS CO., LTD.

Device Number: JMDL-5R8-171

REV: 1.0

5.0mm Round Type LED Lamps

Model No.: 5R94EYC-8BA

ECN: \_\_\_\_\_ Page: 2/5

### Absolute Maximum Ratings at Ta = 25°C

Parameter	Symbol	Rating	Unit	
Forward Current	IF	E-M01	25	mA
		Y-M01	25	
Power Dissipation	Pd	E-M01	100	mW
		Y-M01	100	
Peak Forward Current	IF(Peak)	E-M01	160	mA
		Y-M01	160	
Operating Temperature	Topr	-40 to +85	°C	
Storage Temperature	Tstg	-40 to +100	°C	
Soldering Temperature	Tsol	260 ± 5	°C	
Reverse Voltage	VR	5	V	

Note: \*1:IFP Conditions --Pulse Width ≤ 1msec and Duty ≤ 1/10.

\*2:Soldering time ≤ 5 seconds.

### Electro-Optical Characteristics (Ta=25°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Condition
Luminous Intensity	Iv	E-M01	1500	2000	/	mcd IF= 20 mA
		Y-M01	1500	2000	/	
Peak Wavelength	λ p	E-M01	/	630	/	nm IF= 20 mA
		Y-M01	/	595	/	
Dominant Wavelength	λ d	E-M01	/	622	/	nm IF= 20 mA
		Y-M01	/	590	/	
Spectrum Radiation Bandwidth	Δ λ	E-M01	/	15	/	nm IF= 20 mA
		Y-M01	/	16	/	
Forward Voltage	VF	E-M01	/	2.0	2.5	V IF= 20 mA
		Y-M01	/	2.0	2.5	
Viewing Angle	2 θ 1/2	/	50	/	deg	IF= 20 mA
Reverse Current	IR	/	/	10	μ A	VR= 5 V

Address: Building 2, The First Business Estate, 1th Mingying Rd, shiqidistrict, Zhongshan, Guangdong, China.

TEL : (+86 760) 88323449 88324139

Prepared by : David

FAX : (+86 760) 88321064 88235016

Prepared date : 14/12/16

E-mail: sales @ silsmart.com

M01M01

BZ121010



5.0mm Round Type LED Lamps







Model No.: 5R94EYC-8BA

ECN: \_\_\_\_\_

Page: 3/5

■ Typical Electro-Optical Characteristic Curves:

E-M01



Address: Building 2, The First Business Estate, 1th Mingying Rd, shiqidistrict, Zhongshan, Guangdong, China.

TEL : (+86 760) 88323449 88324139

FAX : (+86 760) 88321064 88235016

E-mail: sales @ silsmart.com

Prepared by: David

Prepared date: 14/12/16

M01M01

BZ121010



5.0mm Round Type LED Lamps







Model No.: 5R94EYC-8BA

ECN: \_\_\_\_\_

Page: 4/5

■ Typical Electro-Optical Characteristic Curves:

Y-M01



Address: Building 2, The First Business Estate, 1th Mingying Rd, shiqidistrict, Zhongshan, Guangdong, China.

TEL : (+86 760) 88323449 88324139

Prepared by : David

FAX : (+86 760) 88321064 88235016

Prepared date : 14/12/16

E-mail: sales @ silsmart.com

M01M01

BZ121010



中山市晶明光电科技有限公司  
ZHONSHAN SILSMART OPTOELECTRONICS CO., LTD.

Device Number: JMDL-5R8-171

REV: 1.0

5.0mm Round Type LED Lamps

Model No.: 5R94EYC-8BA

ECN: \_\_\_\_\_

Page: 5/5

■ Reliability test items and conditions:

NO	Item	Test Conditions	Test Hours/Cycle	Sample size	Ac/Re
1	Solder Heat	TEMP : 260°C ± 5 °C	10 SEC	76 PCS	0/1
2	Temperature Cycle	H : +85°C 15min ∫ 5 min L : -30°C 15min	300 CYCLES	76 PCS	0/1
3	Thermal Shock	H : +85°C 5min ∫ 10 sec L : -10°C 5min	300 CYCLES	76 PCS	0/1
4	High Temperature Storage	TEMP : 100°C	1000 HRS	76 PCS	0/1
5	Low Temperature Storage	TEMP : -40°C	1000 HRS	76 PCS	0/1
6	DC Operating Life	TEMP : 25°C IF = 20mA	1000 HRS	76 PCS	0/1
7	High Temperature/ High Humidity	85°C / 85% RH	1000 HRS	76 PCS	0/1

Address: Building 2, The First Business Estate, 1th Mingying Rd, shiqidistrict, Zhongshan, Guangdong, China.

TEL : (+86 760) 88323449 88324139

FAX : (+86 760) 88321064 88235016

E-mail: sales @ silsmart.com

Prepared date : 14/12/16

Prepared by : David

M01M01 BZ121010