

# **Product Information**

Product series: DF-1859PES-2

**Application description:** Coating composition:

	PES resin
Coating	Coloring pigment
composition	Filler
	Organic solvent

### Coating physical properties:

Solid content (150°C ×30MIN)	30.1±3%	
Specific gravity	1.05~1.10	
Viscosity (Iwata 2# cup)	25.0″±3/25℃	
Covering power	55.5±3m²/L	
Theoretical coating weight (15)	9.66 m²	

#### Coating film properties:

NO.	Items	Detection methods	Results	
1	Gloss	60°glossmeter	10°	
2	Pencil hardness	Chung Hwa pencil	≥3H	
3	Adhesive force	100/100 checks	100/100 5	3M adhesive
	Adhesive force	100/100 checks	times	tape
4	Solvent resistance	MEK wining/ no coore	≥100 次	
	Solveni resistance	MEK wiping/ no scars	≥100 times	
5	Abrasion	/3M scouring pad 1.5KG	≥100 次	
	resistance	pressure	≥100 times	
6	Non-stick	Frying 3 eggs	OK	

### Suggested application methods:

	•				
Applicable	Material pre-	Spraying	Baking	Baking time	
materials	treatment	viscosity	temperature		
Aluminum	Sand	10~12	380℃	10~15MIN	
materials	blasting				

The above experimental data is only for reference, which shall be adjusted according to the actual situation of the production line.

### Other precautions:

A. The coating shall be fully stirred before use and shall be filtered by the 200-mesh filter screen.

<u>DEFFOLON</u> <u>Deffolon Non-stick Coating Co., Ltd.</u>
Address: No.2, No.10 Road, Qijiao Industrial Zone, Maicun Village, Xingtan Town, Shunde District, Foshan City

Tel: 0757-22892248 Fax: 0757-22892249

Website: www.deffolon.com E-mail address: Welch2@deffolon.com



# SHUNDE DEFFOLON NON-STICK COATING CO., LTD

- B. The coating storage temperature is  $10\sim25\,^{\circ}\mathrm{C}$ , and the storage period is 6 months.
- C. The coating diluent is NMP.

<u>DEFFOLON</u> <u>Deffolon Non-stick Coating Co., Ltd.</u>
Address: No.2, No.10 Road, Qijiao Industrial Zone, Maicun Village, Xingtan Town, Shunde District, Foshan City Tel: 0757-22892248
Fax: 0757-22892249

Website: www.deffolon.com E-mail address: Welch2@deffolon.com